



ProtecRite® 7205

PRODUCT DESCRIPTION

A 2 mil LDPE product for general surface protection during light fabrication and/or shipping. The custom formulated acrylic adhesive system offers a "medium adhesion" product with minimal adhesion build even during extended application.

SUGGESTED END USE

Medium Polish Stainless Steel, Anodized Aluminum, Painted Metals, Mill Finish Aluminum

FEATURES

Removable

Conformable

Easy Application

BENEFITS

Clean, stain free removal...even after application for extended periods of time

Lighter gauge backing offers increased conformability and flexibility.

The controlled unwind allows for application using either manual or automatic methods.

PRODUCT SPECIFICATIONS

Total thickness	2.3 mils
Tensile strength	7 lbs/inch
Elongation	300%
Standard roll width (inches)	36", 48", 60"
Standard roll length (yards)	200, 334, 500, 1000
Backing	LDPE
Adhesive type	Acrylic
Color	Clear
Adhesion, pstc 1	6 oz/inch

The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for their intended use under their own operating conditions. Protective Packaging assumes no liability for claims beyond the replacement value of any defective products, and is in no way liable for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.