

PRODUCT DESCRIPTION

A 3 mil LDPE product for surface protection on textured surfaces where a higher adhesion is required. Suitable for protection during shipping and/or moderate fabrication. The product offers a "high adhesion" product with minimal adhesion build.

SUGGESTED END USE

Aircraft Skin Aluminum, Painted Textured Surfaces, Matte Polycarbonate, Synthetic Marble

FEATURES

Removable

Conformable

Easy Application

BENEFITS

Clean, stain free removal... even after application for extended time periods.

Product remains intact... even during extreme bending.

The controlled unwind allows for application using manual or automatic methods.

PRODUCT SPECIFICATIONS

Total thickness	2.8 mils
Tensile strength	8 lbs/inch
Elongation	325%
Standard roll width (inches)	36", 48", 60"
Standard roll length (yards)	200, 334, 500, 1000
Backing	LDPE
Adhesive type	Acrylic
Color	Clear
Adhesion, psc 1	13 oz/inch

The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for their intended use under their own operating conditions. Protective Packaging assumes no liability for claims beyond the replacement value of any defective products, and is in no way liable for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.