



ProtecRite® 7316

PRODUCT DESCRIPTION

A 3 mil LDPE product engineered for protection of textured surfaces or surfaces requiring a higher adhesion product during shipping and/or moderate fabrication. The acrylic adhesive system offers a "high adhesion" product with minimal adhesion build.

SUGGESTED END USE

HP Laminate/Textured, Fabricating Laminates/Satin, Painted "Textured" Steel Aluminum

FEATURES

Removable
Conformable
Easy Application

BENEFITS

Clean, stain free removal... even after application for extended time periods.
Product remains intact... even during excessive bending.
The controlled unwind allows for application using either manual or automatic methods..

PRODUCT SPECIFICATIONS

Total thickness	2.8 mils
Tensile strength	8 lbs/inch
Elongation	325%
Standard roll width (inches)	36", 48", 60"
Standard roll length (yards)	200, 334, 500, 1000
Backing	LDPE
Adhesive type	Acrylic
Color	Clear
Adhesion, psc 1	16 oz/inch

The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for their intended use under their own operating conditions. Protective Packaging assumes no liability for claims beyond the replacement value of any defective products, and is in no way liable for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.