



TransferRite® 6560, 582U, 592U Standard & Ultra™

PRODUCT DESCRIPTION

High grade saturated paper backing with specially formulated latex pressure sensitive (P/S) adhesives for general purpose use as pre-space and application tapes.

TransferRite® Ultra™ products are specially designed for use over ready-to-apply graphics because of improved adhesion to liner.

PRODUCT SPECIFICATIONS

	6560	582U	592U
Typical Uses	<ul style="list-style-type: none"> One-piece decals >24" in one dimension 	<ul style="list-style-type: none"> Pre-spaced lettering >12" high Small one piece decals Mid-sized line striping 	<ul style="list-style-type: none"> Pre-spaced lettering <12" high Fine line striping 4-color process printing Smooth top-coated decals Thermal die cuts
Total thickness	4.3 mils	4.3 mils	4.3 mils
Adhesion to Steel PSTC-101 (180°, oz./in.)	9 (Low)	12 (Medium)	16 (High)
Tensile strength PSTC-31	20 lbs/inch	20 lbs/inch	20 lbs/inch
Elongation PSTC-31	3%	3%	3%

The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for their intended use under their own operating conditions. Protective Packaging assumes no liability for claims beyond the replacement value of any defective products, and is in no way liable for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.